# COBHAM

# SAILOR 500/250 FleetBroadband
## Quick Guide

### Make a voice call

To make a call from your SAILOR FleetBroadband terminal, dial

**00 <country code><phone number> #** or 📞

Example: Cobham SATCOM in Denmark:
**00 45 39558800 #**

**Note**: There are two audio qualities for voice: Standard voice and 3.1 kHz Audio. The default audio quality is Standard voice.

- To force the call to use Standard voice, dial **1 \*** before the number.
- To force the call to use 3.1 kHz Audio, dial **2 \*** before the number.

To make a call **to** the terminal, dial

**+<mobile number>**

**Note**: There are two mobile numbers for voice, one for 3.1 kHz Audio and one for Standard voice.

### Send a fax

To send a fax from the terminal, dial

**00 <country code> <phone number> #**

Example: Cobham SATCOM in Denmark:
**00 45 39558888 #**

**Note**: For an analog fax, the audio quality must be set to 3.1 kHz Audio. For a G.4 ISDN fax, the audio quality must be set to UDI. Note that only SAILOR 500 FleetBroadband supports UDI.

To force 3.1 kHz Audio, dial **2 \*** before the number.

To force UDI, dial **3 \*** before the number.

To send a fax to the terminal, dial

**+<3.1 kHz Audio mobile number>**

Alternatively you can send a fax directly from your PC using an electronic fax application.

### Make a local call

To make local calls between phones connected to the same terminal, do as follows:

- For a local call to an IP handset, dial the number of the IP handset (e.g. **0501**) followed by **#** or 📞 .
- For a local call to an ISDN phone, dial **0401** followed by **#** or 📞 .
- For a local call to an analog phone, dial **0301** or **0302** followed by **#** or 📞 .

For information on allocation of local numbers, refer to the User Manual.

### Access the Internet

To access the Internet do as follows:

1. Connect the LAN cable between your computer and the FleetBroadband terminal.
2. Start up your computer.
3. Open your browser or e-mail program.

For further information, refer to SAILOR 500/250 FleetBroadband Including 19" Rack Version, User manual.